

WIRELESS STB WITH ACCESS POINT ALREADY SET UP

Hook up STB (VIP 2502) to the TV and the plug in AC cord. Make sure the STB has 2" of clearance on the sides and top. Now you are ready to register the STB with the Access Point (VAP 2500)

- When the STB starts up, it will look for a signal from the access point. When it detects the signal, a prompt will appear on the TV screen asking if you wish to connect.
- Press OK button on the front of the STB
- Go to the access point, and then press and hold the WPS button on the front of the VAP for two seconds, then release to activate the WPS process. The access point's WPS LED will blink orange.
- Go back to the TV set and an icon appears on the screen indicating that the connection sequence is in process. When three horizontal dots appear, the connection has been successful.
- On the front panel of the STB, two or more bars on the signal strength indicator should be green.

YOU ARE NOW READY TO PROGRAM THE REMOTE TO CONTROL THE TV

SET UP WIRELESS ACCESS POINT AND WIRELESS STB

Connect the wireless access point to the modem, using an Ethernet cord, by plugging it into an empty LAN port on the back. If you already have three STBs plus internet, you will need to purchase an Ethernet switch. Two existing Cat5 cables for TV should be moved to the switch and the switch and VAP should be plugged into the modem. Plug in the AC cord and the power light should come on.

YOU ARE NOW READY TO SET UP THE WIRELESS STB

Hook up STB (VIP 2502) to the TV and the plug in AC cord. Make sure the STB has 2" of clearance on the sides and top. Now you are ready to register the STB with the Access Point (VAP 2500)

- When the STB starts up, it will look for a signal from the access point. When it detects a signal, a prompt will appear on the TV screen asking if you wish to connect.
- Press OK button on the front of the STB
- Go to the access point, and then press and hold the WPS button on the front of the VAP for two seconds, then release to activate the WPS process. The access point's WPS LED will blink orange.
- Go back to the TV and an icon appears on the screen indicating that the connection sequence is in process. When three horizontal dots appear, the connection has been successful.
- On the front panel of the STB, two or more bars on the signal strength indicator should be green.

YOU ARE NOW READY TO PROGRAM THE REMOTE TO CONTROL THE TV